

## Datablad

080TU0714-6

Druknopkast in PA + glasvezel 70x140x63, zonder gaten, UL



## Kenmerken

|                     |   |
|---------------------|---|
| <b>Bereik</b>       | Druknopkasten, Techno-serie 70x140                        |
| <b>Component</b>    | Deksel zonder gaten                                       |
| <b>Rubriek</b>      | 080TU0714-6   |
| <b>Omschrijving</b> | Druknopkast in PA + glasvezel 70x140x63, zonder gaten, UL |
| <b>Kleur</b>        | Grigio RAL7016 / Grigio RAL7035                           |
| <b>Gewicht</b>      | 182,0   |
| <b>Douanetarief</b> | 85381000  |
| <b>GTIN</b>         | 8052878074241   |

## Technische gegevens

|  |  |
|--|--|
| <b>Approvals</b>                         | CE, UL, CSA, EAC                                   |
| <b>Compliance with standards</b>         | IEC-EN62208, UL508, CSA C22.2 No.14-13             |
| <b>Operating temperatures</b>            | -35° ÷ +80°C                                       |
| <b>Protection against impact</b>         | IK09 (IEC-EN62262)                                 |
| <b>Protection degree</b>                 | IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250) |
| <b>Enclosure material</b>                | PA Polyamide - glass fiber reinforced              |
| <b>Gasket material</b>                   | TPE thermoplastic elastomer                        |
| <b>Screw material</b>                    | Stainless steel AISI 304                           |
| <b>Screw type</b>                        | Torx T15 slotted head type                         |
| <b>Enclosure thickness</b>               | 3,5mm  |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                        |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                             |
| <b>Combustion behaviour</b>              | 5VA (UL50 - UL746C)                                |
| <b>Combustion behaviour</b>              | 960°(IEC-EN60695-2-11)                             |
| <b>Combustion behaviour</b>              | V0 (UL94)  |
| <b>Fitted for outdoor application</b>    | yes  |
| <b>Warranty period</b>                   | 18 months  |

## Technische tekeningen

