

## Hoja de datos

080TU0718-6

Caja pulsadora in PA + fibra de vidrio 70x180x63, sin orificios, UL



## Características

<b>Rango</b>	Cajas pulsadoras, serie Techno 70x180
<b>Componente</b>	Tapa sin orificios
<b>Código</b>	080TU0718-6
<b>Descripción</b>	Caja pulsadora in PA + fibra de vidrio 70x180x63, sin orificios, UL
<b>Color</b>	Grigio RAL7016 / Grigio RAL7035
<b>Peso</b>	222,0
<b>Arancel aduanero</b>	85381000
<b>GTIN</b>	8052878074340

## Datos técnicos

<b>Approvals</b>	CE, UL, CSA, EAC
<b>Compliance with standards</b>	IEC-EN62208, UL508, CSA C22.2 No.14-13
<b>Operating temperatures</b>	-35° ÷ +80°C
<b>Protection against impact</b>	IK09 (IEC-EN62262)
<b>Protection degree</b>	IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250)
<b>Enclosure material</b>	PA Polyamide - glass fiber reinforced
<b>Gasket material</b>	TPE thermoplastic elastomer
<b>Screw material</b>	Stainless steel AISI 304
<b>Screw type</b>	Torx T15 slotted head type
<b>Enclosure thickness</b>	3,5mm
<b>Tightening torque</b>	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Combustion behaviour</b>	5VA (UL50 - UL746C)
<b>Combustion behaviour</b>	960°(IEC-EN60695-2-11)
<b>Combustion behaviour</b>	V0 (UL94)
<b>Fitted for outdoor application</b>	yes
<b>Warranty period</b>	18 months

# Dibujos técnicos

