


Datablad

080TU0718-6P5L

Drukknopkast in PA + glasvezel 70x180x63, 5 gaten d22, UL



Kenmerken

Bereik	Drukknopkasten, Techno-serie 70x180
Component	Deksel met 5 gaten D22
Rubriek	080TU0718-6P5L
Omschrijving	Drukknopkast in PA + glasvezel 70x180x63, 5 gaten d22, UL
Kleur	Grigio RAL7016 / Grigio RAL7035
Gewicht	222,0
Douanetarief	85381000
GTIN	8052878074401

Technische gegevens

Approvals	CE, UL, CSA, EAC
Compliance with standards	IEC-EN62208, UL508, CSA C22.2 No.14-13
Operating temperatures	-35° ÷ +80°C
Protection against impact	IK09 (IEC-EN62262)
Protection degree	IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250)
Enclosure material	PA Polyamide - glass fiber reinforced
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Enclosure thickness	3,5mm
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	960°(IEC-EN60695-2-11)
Combustion behaviour	V0 (UL94)
Fitted for outdoor application	yes
Warranty period	18 months

Technische tekeningen

