


## Hoja de datos

080TU0727-6P7LC

Caja pulsadora in PA + fibra de vidrio 70x267x63, 7 orificios d22, UL



## Características

|                  |   |
|------------------|---|
| Rango            | Cajas pulsadoras, serie Techno 70x267                                 |
| Componente       | Tapa con 7 orificios D22  |
| Código           | 080TU0727-6P7LC   |
| Descripción      | Caja pulsadora in PA + fibra de vidrio 70x267x63, 7 orificios d22, UL |
| Color            | Grigio RAL7016 / Grigio RAL7035                                       |
| Peso             | 315,0   |
| Arancel aduanero | 85381000  |
| GTIN             | 8052878075927   |

## Datos técnicos

|                                   |  |
|-----------------------------------|--|
| Approvals                         | CE, UL, CSA, EAC                                   |
| Compliance with standards         | IEC-EN62208, UL508, CSA C22.2 No.14-13             |
| Operating temperatures            | -35° ÷ +80°C                                       |
| Protection against impact         | IK09 (IEC-EN62262)                                 |
| Protection degree                 | IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250) |
| Enclosure material                | PA Polyamide - glass fiber reinforced              |
| Gasket material                   | TPE thermoplastic elastomer                        |
| Screw material                    | Stainless steel AISI 304                           |
| Screw type                        | Torx T15 slotted head type                         |
| Enclosure thickness               | 3,5mm  |
| Tightening torque                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                        |
| Protection against electric shock | Class II (IEC-EN61140)                             |
| Combustion behaviour              | 5VA (UL50 - UL746C)                                |
| Combustion behaviour              | 960°(IEC-EN60695-2-11)                             |
| Combustion behaviour              | V0 (UL94)  |
| Fitted for outdoor application    | yes  |
| Warranty period                   | 18 months  |

## Dibujos técnicos

