

Scheda Dati

080TU0727-6T

Drukknopkast in PA + glasvezel 70x267x63, zonder gaten, transparant, UL



Caratteristiche

Bereik	Drukknopkasten, Techno-serie 70x267
Componente	Deksel zonder gaten
Rubriek	080TU0727-6T
Omschrijving	Drukknopkast in PA + glasvezel 70x267x63, zonder gaten, transparant, UL
Peso	113,0
Tariffa doganale	85381000
GTIN	8052878076801

Dati tecnici

Approvals	CE, UL, CSA, EAC
Compliance with standards	IEC-EN62208, UL508, CSA C22.2 No.14-13
Operating temperatures	-35° ÷ +80°C
Protection against impact	IK09 (IEC-EN62262)
Protection degree	IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250)
Lid material	PC Polycarbonate
Enclosure material	PA Polyamide - glass fiber reinforced
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Enclosure thickness	3,5mm
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	V-2 (UL94)
Combustion behaviour	960°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Warranty period	18 months

Disegni tecnici

