


## Fiche technique

080TU0914-7T

Boîte à boutons in PA + fibre verre 90x140x74, sans trous, transparent, UL



## Caractéristiques

|                                     |  |
|-------------------------------------|--|
| <b>Portée</b>                       | Boîtes à boutons, série Techno 90x140                                      |
| <b>Composant</b>                    | Couvercle sans trous   |
| <b>Code</b>                         | 080TU0914-7T   |
| <b>Désignation des marchandises</b> | Boîte à boutons in PA + fibre verre 90x140x74, sans trous, transparent, UL |
| <b>Couleur</b>                      | Trasparente / Grigio RAL7035   |
| <b>Poids</b>                        | 292,0  |
| <b>Tarif douanier</b>               | 85381000   |
| <b>GTIN</b>                         | 8052878075644  |

## Données techniques

|  |                                       |
|--|---------------------------------------|
| <b>Approvals</b>                         | CE, UL, CSA, EAC                      |
| <b>Compliance with standards</b>         | IEC-EN62208, UL50, UL50E              |
| <b>Operating temperatures</b>            | -35° ÷ +80°C                          |
| <b>Protection degree</b>                 | IP67 - IP69 (IEC-EN60529)             |
| <b>Protection against impact</b>         | IK09 (IEC-EN62262)                    |
| <b>Lid material</b>                      | PC Polycarbonate                      |
| <b>Enclosure material</b>                | PA Polyamide - glass fiber reinforced |
| <b>Gasket material</b>                   | TPE thermoplastic elastomer           |
| <b>Screw material</b>                    | Stainless steel AISI 304              |
| <b>Screw type</b>                        | HEX 3 slotted head - M4 thread        |
| <b>Threaded bushing material</b>         | Stainless steel AISI 304 - M4 thread  |
| <b>Enclosure thickness</b>               | 3,5mm                                 |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)           |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                |
| <b>Halogen-free</b>                      | yes                                   |
| <b>Combustion behaviour</b>              | 5VA (UL50 - UL746C)                   |
| <b>Combustion behaviour</b>              | V-2 (UL94)                            |
| <b>Combustion behaviour</b>              | 960°(IEC-EN60695-2-11)                |
| <b>Fitted for outdoor application</b>    | yes                                   |
| <b>Warranty period</b>                   | 18 months                             |

## Dessins techniques

---

