

## Datenblatt

080TU0918-7

Drucktastergehäuse in PA + Glasfaser 90x180x74, ungebohrt, UL



## Merkmale

|                        |   |
|------------------------|---|
| <b>Baureihe</b>        | Drucktastergehäuse, Serie Techno 90x180                       |
| <b>Komponenten</b>     | Deckel ungebohrt  |
| <b>Artikel-Nr.</b>     | 080TU0918-7   |
| <b>Beschreibung</b>    | Drucktastergehäuse in PA + Glasfaser 90x180x74, ungebohrt, UL |
| <b>Farbe</b>           | Grigio RAL7016 / Grigio RAL7035                               |
| <b>Gewicht - gr</b>    | 388,0   |
| <b>Zolltarifnummer</b> | 85381000  |
| <b>GTIN</b>            | 8052878074760   |

## Technische Daten

|  |                                       |
|--|---------------------------------------|
| <b>Approvals</b>                         | CE, UL, CSA, EAC                      |
| <b>Compliance with standards</b>         | IEC-EN62208, UL50, UL50E              |
| <b>Operating temperatures</b>            | -35° ÷ +80°C                          |
| <b>Protection degree</b>                 | IP67 - IP69 (IEC-EN60529)             |
| <b>Protection against impact</b>         | IK09 (IEC-EN62262)                    |
| <b>Enclosure material</b>                | PA Polyamide - glass fiber reinforced |
| <b>Gasket material</b>                   | TPE thermoplastic elastomer           |
| <b>Screw material</b>                    | Stainless steel AISI 304              |
| <b>Screw type</b>                        | HEX 3 slotted head - M4 thread        |
| <b>Threaded bushing material</b>         | Stainless steel AISI 304 - M4 thread  |
| <b>Enclosure thickness</b>               | 3,5mm                                 |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)           |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                |
| <b>Halogen-free</b>                      | yes                                   |
| <b>Combustion behaviour</b>              | 5VA (UL50 - UL746C)                   |
| <b>Combustion behaviour</b>              | 960°(IEC-EN60695-2-11)                |
| <b>Combustion behaviour</b>              | V0 (UL94)                             |
| <b>Fitted for outdoor application</b>    | yes                                   |
| <b>Warranty period</b>                   | 18 months                             |

## Technische Zeichnungen

---

