

Datasheet

080TU0918-7S3

Push-button box in PA + glass fibre 90x180x74, 3 holes d30 , UL



Features

| | |
|-----------------------|---|
| Range | Push-button boxes, Techno series 90x180 |
| components | Cover with 3 holes D30 |
| Code | 080TU0918-7S3 |
| Description | Push-button box in PA + glass fibre 90x180x74, 3 holes d30 , UL |
| Colour | Grigio RAL7016 / Grigio RAL7035 |
| Weight - gr | 226.0 |
| Customs Tariff | 85381000 |
| GTIN | 8052878075118 |

Datasheet

| | |
|--|---------------------------------------|
| Approvals | CE, UL, CSA, EAC |
| Compliance with standards | IEC-EN62208, UL50, UL50E |
| Operating temperatures | -35° ÷ +80°C |
| Protection degree | IP67 - IP69 (IEC-EN60529) |
| Protection against impact | IK09 (IEC-EN62262) |
| Enclosure material | PA Polyamide - glass fiber reinforced |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | HEX 3 slotted head - M4 thread |
| Threaded bushing material | Stainless steel AISI 304 - M4 thread |
| Enclosure thickness | 3,5mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Halogen-free | yes |
| Combustion behaviour | 5VA (UL50 - UL746C) |
| Combustion behaviour | 960°(IEC-EN60695-2-11) |
| Combustion behaviour | V0 (UL94) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Technical drawings

