


## Scheda Dati

080TU0927-7P8L

Scatola pulsantiera in poliammide rinforzato 90x267x74, 8 fori d22, SUL



## Caratteristiche

<b>Gamma</b>	Scatole pulsantiera serie Techno 90x267 mm
<b>Componente</b>	Coperchio con 8 fori D22
<b>Codice</b>	080TU0927-7P8L
<b>Descrizione</b>	Scatola pulsantiera in poliammide rinforzato 90x267x74, 8
<b>Colore</b>	Grigio RAL7016 / Grigio RAL7035
<b>Peso</b>	226,0
<b>Tariffa doganale</b>	85381000
<b>GTIN</b>	8052878076627

## Dati tecnici

<b>Approvals</b>	CE, UL, CSA, EAC
<b>Compliance with standards</b>	IEC-EN62208, UL50, UL50E
<b>Operating temperatures</b>	-35° ÷ +80°C
<b>Protection degree</b>	IP67 - IP69 (IEC-EN60529)
<b>Protection against impact</b>	IK09 (IEC-EN62262)
<b>Enclosure material</b>	PA Polyamide - glass fiber reinforced
<b>Gasket material</b>	TPE thermoplastic elastomer
<b>Screw material</b>	Stainless steel AISI 304
<b>Screw type</b>	HEX 3 slotted head - M4 thread
<b>Threaded bushing material</b>	Stainless steel AISI 304 - M4 thread
<b>Enclosure thickness</b>	3,5mm
<b>Tightening torque</b>	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Halogen-free</b>	yes
<b>Combustion behaviour</b>	5VA (UL50 - UL746C)
<b>Combustion behaviour</b>	960°(IEC-EN60695-2-11)
<b>Combustion behaviour</b>	V0 (UL94)
<b>Fitted for outdoor application</b>	yes
<b>Warranty period</b>	18 months

## Disegni tecnici

