

# Datablad

080TU0927-9G

Drukknopkast in PA + glasvezel 90x267x94, zonder gaten, geel, UL



## Kenmerken

|              |                                                                  |
|--------------|------------------------------------------------------------------|
| Bereik       | Drukknopkasten, Techno-serie 90x267                              |
| Component    | Deksel zonder gaten                                              |
| Rubriek      | 080TU0927-9G                                                     |
| Omschrijving | Drukknopkast in PA + glasvezel 90x267x94, zonder gaten, geel, UL |
| Kleur        | Giallo RAL1003 / Grigio RAL7035                                  |
| Gewicht      | 0,0                                                              |
| Douanetarief | 85381000                                                         |
| GTIN         | 8052878080631                                                    |

## Technische gegevens

|                                   |                                                    |
|-----------------------------------|----------------------------------------------------|
| Approvals                         | CE, UL, CSA, EAC                                   |
| Compliance with standards         | IEC-EN62208, UL508, CSA C22.2 No.14-13             |
| Operating temperatures            | -35° ÷ +80°C                                       |
| Protection against impact         | IK08 (IEC-EN62262)                                 |
| Protection degree                 | IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250) |
| Enclosure material                | PA Polyamide - glass fiber reinforced              |
| Gasket material                   | TPE thermoplastic elastomer                        |
| Screw material                    | Stainless steel AISI 304                           |
| Screw type                        | HEX 3 slotted head - M4 thread                     |
| Threaded bushing material         | Stainless steel AISI 304 - M4 thread               |
| Enclosure thickness               | 3,5mm                                              |
| Tightening torque                 | 0.8 ÷ 1.2 Nm (7.1 ÷ 10.6 Lb-in)                    |
| Protection against electric shock | Class II (IEC-EN61140)                             |
| Heavy metal-free                  | yes                                                |
| PVC-free                          | yes                                                |
| Silicon-free                      | yes                                                |
| Halogen-free                      | yes                                                |
| Combustion behaviour              | 960°(IEC-EN60695-2-12)                             |
| Fitted for outdoor application    | yes                                                |
| Combustion behaviour              | 5VA (UL94)                                         |

Warranty period

18 months

# Technische tekeningen

