

## Scheda Dati

080TU0927-9P7C

Scatola pulsantiera in poliammide rinforzato 90x267x94, 7 fori d22, UL



## Caratteristiche

|                  |                                                           |
|------------------|-----------------------------------------------------------|
| Gamma            | Scatole pulsantiere serie Techno 90x267 mm                |
| Componente       | Coperchio con 7 fori D22                                  |
| Codice           | 080TU0927-9P7C                                            |
| Descrizione      | Scatola pulsantiera in poliammide rinforzato 90x267x94, 7 |
| Colore           | Grigio RAL7016 / Grigio RAL7035                           |
| Peso             | 0,0                                                       |
| Tariffa doganale | 85381000                                                  |
| GTIN             | 8052878080723                                             |

## Dati tecnici

|                                   |                                                    |
|-----------------------------------|----------------------------------------------------|
| Approvals                         | CE, UL, CSA, EAC                                   |
| Compliance with standards         | IEC-EN62208, UL508, CSA C22.2 No.14-13             |
| Operating temperatures            | -35° ÷ +80°C                                       |
| Protection against impact         | IK08 (IEC-EN62262)                                 |
| Protection degree                 | IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250) |
| Enclosure material                | PA Polyamide - glass fiber reinforced              |
| Gasket material                   | TPE thermoplastic elastomer                        |
| Screw material                    | Stainless steel AISI 304                           |
| Screw type                        | HEX 3 slotted head - M4 thread                     |
| Threaded bushing material         | Stainless steel AISI 304 - M4 thread               |
| Enclosure thickness               | 3,5mm                                              |
| Tightening torque                 | 0.8 ÷ 1.2 Nm (7.1 ÷ 10.6 Lb-in)                    |
| Protection against electric shock | Class II (IEC-EN61140)                             |
| Heavy metal-free                  | yes                                                |
| PVC-free                          | yes                                                |
| Silicon-free                      | yes                                                |
| Halogen-free                      | yes                                                |
| Combustion behaviour              | 960°(IEC-EN60695-2-12)                             |
| Fitted for outdoor application    | yes                                                |
| Combustion behaviour              | 5VA (UL94)                                         |
| Warranty period                   | 18 months                                          |

# Disegni tecnici

