


# Datasheet

080TU0927-9P7LC  
Push-button box in PA + glass fibre 90x267x94, 7 holes d22 , UL



## Features

|                |                                                                 |
|----------------|-----------------------------------------------------------------|
| Range          | Push-button boxes, Techno series 90x267                         |
| components     | Cover with 7 holes D22                                          |
| Code           | 080TU0927-9P7LC                                                 |
| Description    | Push-button box in PA + glass fibre 90x267x94, 7 holes d22 , UL |
| Colour         | Grigio RAL7016 / Grigio RAL7035                                 |
| Weight - gr    | 0.0                                                             |
| Customs Tariff | 85381000                                                        |
| GTIN           | 8052878080754                                                   |

## Datasheet

|                                   |                                                    |
|-----------------------------------|----------------------------------------------------|
| Approvals                         | CE, UL, CSA, EAC                                   |
| Compliance with standards         | IEC-EN62208, UL508, CSA C22.2 No.14-13             |
| Operating temperatures            | -35° ÷ +80°C                                       |
| Protection against impact         | IK08 (IEC-EN62262)                                 |
| Protection degree                 | IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250) |
| Enclosure material                | PA Polyamide - glass fiber reinforced              |
| Gasket material                   | TPE thermoplastic elastomer                        |
| Screw material                    | Stainless steel AISI 304                           |
| Screw type                        | HEX 3 slotted head - M4 thread                     |
| Threaded bushing material         | Stainless steel AISI 304 - M4 thread               |
| Enclosure thickness               | 3,5mm                                              |
| Tightening torque                 | 0.8 ÷ 1.2 Nm (7.1 ÷ 10.6 Lb-in)                    |
| Protection against electric shock | Class II (IEC-EN61140)                             |
| Heavy metal-free                  | yes                                                |
| PVC-free                          | yes                                                |
| Silicon-free                      | yes                                                |
| Halogen-free                      | yes                                                |
| Combustion behaviour              | 960°(IEC-EN60695-2-12)                             |
| Fitted for outdoor application    | yes                                                |
| Combustion behaviour              | 5VA (UL94)                                         |

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

# Technical drawings

