

Datablad

080TU1818-9P12

Drukknopkast in PA + glasvezel 180x180x94, 12 gaten d22, UL



Kenmerken

Bereik	Drukknopkasten, Techno-serie 180x180
Component	Deksel met 12 gaten D22
Rubriek	080TU1818-9P12
Omschrijving	Drukknopkast in PA + glasvezel 180x180x94, 12 gaten d22, UL
Kleur	Grigio RAL7016 / Grigio RAL7035
Gewicht	564,0
Douanetarief	85381000
GTIN	8052878077143

Technische gegevens

Approvals	CE, UL, CSA, EAC
Compliance with standards	IEC-EN62208, UL50, UL50E
Operating temperatures	-35° ÷ +80°C
Protection degree	IP67 - IP69 (IEC-EN60529)
Protection against impact	IK09 (IEC-EN62262)
Enclosure material	PA Polyamide - glass fiber reinforced
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	HEX 3 slotted head - M4 thread
Threaded bushing material	Stainless steel AISI 304 - M4 thread
Enclosure thickness	3,5mm
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Halogen-free	yes
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	960°(IEC-EN60695-2-11)
Combustion behaviour	V0 (UL94)
Fitted for outdoor application	yes
Warranty period	18 months

Technische tekeningen

