

Scheda Dati

080TU1827-9P16

Scatola pulsantiera in poliammide rinforzato 180x267x94, 1 6 fori d22, UL



Caratteristiche

| | |
|-------------------------|--|
| Gamma | Scatole pulsantiera serie Techno 180x267 mm |
| Componente | Coperchio con 16 fori D22 |
| Codice | 080TU1827-9P16 |
| Descrizione | Scatola pulsantiera in poliammide rinforzato 180x267x94, 1 |
| Colore | Grigio RAL7016 / Grigio RAL7035 |
| Peso | 564,0 |
| Tariffa doganale | 85381000 |
| GTIN | 8052878078058 |

Dati tecnici

| | |
|--|---------------------------------------|
| Approvals | CE, UL, CSA, EAC |
| Compliance with standards | IEC-EN62208, UL50, UL50E |
| Operating temperatures | -35° ÷ +80°C |
| Protection degree | IP67 - IP69 (IEC-EN60529) |
| Protection against impact | IK09 (IEC-EN62262) |
| Enclosure material | PA Polyamide - glass fiber reinforced |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | HEX 3 slotted head - M4 thread |
| Threaded bushing material | Stainless steel AISI 304 - M4 thread |
| Enclosure thickness | 3,5mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Halogen-free | yes |
| Combustion behaviour | 5VA (UL50 - UL746C) |
| Combustion behaviour | 960°(IEC-EN60695-2-11) |
| Combustion behaviour | V0 (UL94) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Disegni tecnici

