

## Scheda Dati

080TU1827-9S9

Scatola pulsantiera in poliammide rinforzato 180x267x94, 9 fori d30, UL



## Caratteristiche

|                         |  |
|-------------------------|--|
| <b>Gamma</b>            | Scatole pulsantiera serie Techno 180x267 mm                |
| <b>Componente</b>       | Coperchio con 9 fori D30                                   |
| <b>Codice</b>           | 080TU1827-9S9  |
| <b>Descrizione</b>      | Scatola pulsantiera in poliammide rinforzato 180x267x94, 9 |
| <b>Colore</b>           | Grigio RAL7016 / Grigio RAL7035                            |
| <b>Peso</b>             | 564,0  |
| <b>Tariffa doganale</b> | 85381000   |
| <b>GTIN</b>             | 8052878077389  |

## Dati tecnici

|  |                                       |
|--|---------------------------------------|
| <b>Approvals</b>                         | CE, UL, CSA, EAC                      |
| <b>Compliance with standards</b>         | IEC-EN62208, UL50, UL50E              |
| <b>Operating temperatures</b>            | -35° ÷ +80°C                          |
| <b>Protection degree</b>                 | IP67 - IP69 (IEC-EN60529)             |
| <b>Protection against impact</b>         | IK09 (IEC-EN62262)                    |
| <b>Enclosure material</b>                | PA Polyamide - glass fiber reinforced |
| <b>Gasket material</b>                   | TPE thermoplastic elastomer           |
| <b>Screw material</b>                    | Stainless steel AISI 304              |
| <b>Screw type</b>                        | HEX 3 slotted head - M4 thread        |
| <b>Threaded bushing material</b>         | Stainless steel AISI 304 - M4 thread  |
| <b>Enclosure thickness</b>               | 3,5mm                                 |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)           |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                |
| <b>Halogen-free</b>                      | yes                                   |
| <b>Combustion behaviour</b>              | 5VA (UL50 - UL746C)                   |
| <b>Combustion behaviour</b>              | 960°(IEC-EN60695-2-11)                |
| <b>Combustion behaviour</b>              | V0 (UL94)                             |
| <b>Fitted for outdoor application</b>    | yes                                   |
| <b>Warranty period</b>                   | 18 months                             |

## Disegni tecnici

