

Datablad

080TU1827-9T

Drukknopkast in PA + glasvezel 180x267x94, zonder gaten, transparant, UL



Kenmerken

| | |
|---------------------|--|
| Bereik | Drukknopkasten, Techno-serie 180x267 |
| Component | Deksel zonder gaten |
| Rubriek | 080TU1827-9T |
| Omschrijving | Drukknopkast in PA + glasvezel 180x267x94, zonder gaten, transparant, UL |
| Kleur | Trasparente / Grigio RAL7035 |
| Gewicht | 564,0 |
| Douanetarief | 85381000 |
| GTIN | 8052878075866 |

Technische gegevens

| | |
|--|---------------------------------------|
| Approvals | CE, UL, CSA, EAC |
| Compliance with standards | IEC-EN62208, UL50, UL50E |
| Operating temperatures | -35° ÷ +80°C |
| Protection degree | IP67 - IP69 (IEC-EN60529) |
| Protection against impact | IK09 (IEC-EN62262) |
| Lid material | PC Polycarbonate |
| Enclosure material | PA Polyamide - glass fiber reinforced |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | HEX 3 slotted head - M4 thread |
| Threaded bushing material | Stainless steel AISI 304 - M4 thread |
| Enclosure thickness | 3,5mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Halogen-free | yes |
| Combustion behaviour | 5VA (UL50 - UL746C) |
| Combustion behaviour | V-2 (UL94) |
| Combustion behaviour | 960°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Technische tekeningen

