

Scheda Dati

080V2621-12SP

Panel display con soporte L 125mm sin placa frontal



Caratteristiche

| | |
|------------------|---|
| Rango | Panel display |
| Componente | Caja botonera sin placa |
| Código | 080V2621-12SP |
| Descripción | Panel display con soporte L 125mm sin placa frontal |
| Color | Grigio RAL7016 |
| Peso | 700,0 |
| Tariffa doganale | 85381000 |
| GTIN | 8052878068196 |

Dati tecnici

| | |
|-----------------------------------|--|
| Approvals | CE |
| Compliance with standards | IEC-EN62208 |
| Operating temperatures | -35° ÷ +80°C |
| Protection degree | IP65 (IEC-EN60529) |
| Protection against impact | IK05 (IEC-EN62262) |
| Housing material | PA Polyamide |
| Manufacturing process | Injection moulding |
| Screw material | Stainless steel AISI 304 |
| Front plate material | PMMA polymethylmethacrylate |
| Front plate | Thickness 3mm when included |
| Customized front plate | 080VPFP-Dxx customized drilling by laser cutting |
| Tightening torque | 0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Cable entry | By M20 PA flexible pipe - 300mm lenght |
| Adjustable arm | Two different lenght 125mm - 185mm |
| Warranty period | 18 months |

Disegni tecnici

