

## Fiche technique

080V2621-12SP

Boîtier à bouton-poussoir avec support L 125mm sans plaque avant



## Caractéristiques

<b>Portée</b>	Boîtier moniteur
<b>Composant</b>	Boîtier à boutons poussoir sans plaque
<b>Code</b>	080V2621-12SP
<b>Désignation des marchandises</b>	Boîtier à bouton-poussoir avec support L 125mm sans plaque avant
<b>Couleur</b>	Grigio RAL7016
<b>Poids</b>	700,0
<b>Tarif douanier</b>	85381000
<b>GTIN</b>	8052878068196

## Données techniques

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN62208
<b>Operating temperatures</b>	-35° ÷ +80°C
<b>Protection degree</b>	IP65 (IEC-EN60529)
<b>Protection against impact</b>	IK05 (IEC-EN62262)
<b>Housing material</b>	PA Polyamide
<b>Manufacturing process</b>	Injection moulding
<b>Screw material</b>	Stainless steel AISI 304
<b>Front plate material</b>	PMMA polymethylmethacrylate
<b>Front plate</b>	Thickness 3mm when included
<b>Customized front plate</b>	080VPFP-Dxx customized drilling by laser cutting
<b>Tightening torque</b>	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Cable entry</b>	By M20 PA flexible pipe - 300mm lenght
<b>Adjustable arm</b>	Two different lenght 125mm - 185mm
<b>Warranty period</b>	18 months

## Dessins techniques

